

The New BT-2G Tablet from Hitachi

- teach or present from anywhere in the room



The StarBoard BT-2 is a lightweight graphics tablet that when connected to a projector and PC, enables presentations to be displayed on a large screen and the computer to be controlled remotely from anywhere in the room. A cordless pen is used to annotate onto the tablet, which communicates wirelessly with an adaptor connected to the computer's USB port.

Portable inspiration

The StarBoard BT-2 tablet is ideal for use during a lesson, training session or meeting. By moving the pen across the surface of the tablet, the user can control the mouse movements of the PC. The pen facilitates both left and right mouse clicks, removing the need to use the PC directly. Several tablets can be used in a session if desired, so that different people can interact with the computer when control is transferred to them. The new tablet features 12 function buttons, making it very simple to operate.

Like all Hitachi interactive products, the new StarBoard BT-2 tablet is RoHS compliant (restriction of hazardous substances).



HITACHI
Inspire the Next

The New BT-2G Tablet from Hitachi

- teach or present from anywhere in the room

Technical Specifications

Technology	Electromagnetic
Dimensions (mm)	239mm (W) x 251mm (H) x 30mm (D)
Active area	6 x 4.5 inches (152 mm (W) x 114mm (H))
Connection Interface (Wireless/Wired)	Bluetooth 1.2 (class II)/USB 1.1 Full speed
Connection Distance	20 meters
Input Methods	Induction
Resolution	1000 Lpi
Sampling Rate (Wireless/Wired)	162 points/s/183 points/s
Function button	12 (Hold 1.5 seconds to work)
Weight (without/with batteries)	493g/545g
Hot key	1 (for Bluetooth unpairing)
Power supply (Wireless)	1.2V AA battery x 2 (Rechargeable battery suggested)
(Wired)	USB bus power (No batteries needed)
Battery life	Continual mode 24hrs

Pen	5V Pen
Battery	AAA battery x 1 (1.5V)
Battery life	Approximately 1800 hours
Proximity	8mm
Pen feature On/Off switch, 2 Side Buttons, Power Saving Mode, Low Battery Indicator LED	

Operating Temperature	0 - 40°C
Operating Humidity	20 - 80 %
Safety Standard approvals	CE, FCC
Parallel usage	Up to 7 devices per PC (Wireless mode)
Warranty	1 year

Specification Items	BTU02 (Class II) Standard
Interface	USB 2.0 (type A)
RF Range	Up to 40m (limited condition)
Security	Pairing, Encryption, Authentication
Power	USB bus power (LED indicator for checking power status)
Dimensions (mm)	58.5mm (W) x 17mm (H) x 8 mm (D)
Weight	6.8g

System Requirements

Pentium II 300MHz (800MHz or faster recommended)
RAM 128MB (256MB or higher recommended)
HDD 200MB of free space
Windows Operating System Windows 2000, Windows XP (latest service pack recommended)



The StarBoard BT-2 pad is ideal for use during a lesson, training session or meeting.

Hitachi Software Engineering (UK) Limited
Interactive Media Solutions Division
Hillgate House, 26 Old Bailey
London EC4M 7HW, United Kingdom
Tel: +44 (0)20 7246 6868; Fax: +44 (0)20 7246 6860
Email: sales@hitachi-software.co.uk

Hitachi Software Engineering France S.A.S.
Interactive Media Solutions Division
7ème étage, 64 rue du Dessous des Berges
75013 Paris, France
Tel: +33 (0) 153 827 600; Fax: +33 (0) 153 827 619
Email: starboard@hitachisoft-eu.com

Hitachi Software Engineering Europe AG
Interactive Media Solutions Division
Kurfürstendamm 22
D-10719 Berlin, Germany
Tel: +49 (0)30 8877 2600; Fax: +49 (0)30 8877 2610
Email: starboard@hitachisoft.de

www.hitachisoft-eu.com

Further information:

HITACHI
Inspire the Next